

LOGLIFE matt



Sustainable development and production



EMAS:

- Continuous improvement of environmental performance
- Annual sustainability report
- Energy and water management
- Social Fairness



DIN ISO 14001:

- Continuous improvement in reducing waste and CO2 emissions, and saving of energy, water and material consumption



ISO 50001:

- Continuous improvement of energy management: performance, efficiency, security, use and consumption



A.I.S.E.-Charter:

- Safe and sustainable manufacturing of cleaning products



DIN ISO 9001:

- Continuous improvement of management processes and customer satisfaction
- Established quality management system in product development and production

green-Effective® High-performance matt floor polish

■ Eco-efficient performance with eco-effective product design

User and environmental safety at the highest cleaning performance



- Developed to fulfil the Austrian Ecolabel
- Complete abandonment of toxic and harmful materials
- Outperforms other products at lower use concentration

Intensive use of renewable resources – continuous increase of the reutilisation score



- Production under extensive use of renewable raw materials and energy using to 100% hydroelectric, solar and geothermic power
- Active water stewardship maintaining an own fresh and waste water treatment

Full transparency - complete ingredient declaration

<5% Anionic surfactants, Non-ionic surfactants, SODIUM PYRITHIONE, METHYLISOTHIAZOLINONE, BENZISOTHIAZOLINONE

Specific ingredients: water, acrylic-styrene copolymer, polyethylene wax, matting agent, glycol ether, softening agent (TBEP-free), levelling agents (non-fluorinated)

Traditional German quality - driving your durable business development



- More than 25 years pioneer in sustainable product development
- Smart hygiene solutions ensuring profitable growth
- Trusted brand

Professional user training and on-site support for Sustainable Hygiene Solutions



- Comprehensive knowledge transfer through qualified cleaning consultants
- Customized hygiene plans and cleaning recommendations optimizing your business and cleaning procedures
- Increased service value and strengthened company reputation



makes the difference

LONGLIFE matt



green-Effective® High-performance matt floor polish

■ Resistant ■ Matt appearance ■ Increased safety

Product profile

- LONGLIFE matt is a high-performance dispersion providing excellent results.
- LONGLIFE matt ensures outstanding durability, and resistance thanks to special developed technology.
- The use of special polymers prevents clouding of protective film after maintenance cleaning.
- Thanks to a very good alcohol, and disinfectant resistance as well as slip-resistance, LONGLIFE matt is particularly suitable for use in health facilities, and wherever a matt appearance is required.
- Slip-resistance is certified in accordance with DIN 18032-2.
- Protective film provided by LONGLIFE matt ensures outstanding resistance while having highly elastic properties, and extraordinary adherence on all flooring types.
- Owing its special characteristics LONGLIFE matt can also be applied on residual damp linoleum floors. A renewal of protective film is possible without significant increase of gloss level.
- This product works ideally in a system with LINAX complete, which easily removes LONGLIFE matt polymer films.
- By the complete abandonment of hazardous ingredients such as zinc, TBEP, perfume, and fluorinated levelling agents, LONGLIFE matt takes on the responsibility for future generations.

Area of application

- LONGLIFE matt is suitable for universal use on all coatable flooring especially elastic flooring made of PVC, linoleum, natural rubber and other special synthetic materials.
- Specially recommended for highly frequented areas, e.g. hospitals, nursing home, medical practice etc., where semi matt coatings with high durability and high slip resistance are required.
- Not to be used on polished stone floors, stoneware tiles, as well as on unsealed wood.

Product safety, storage and environmental instructions

Safety: For professional use only. Do not mix with other products. Test material compatibility before use. For further information, see Safety Data Sheet.

Storage: Store at room temperature in the original container. Keep from freezing.

Environmental: Only give completely emptied packaging in the recommended waste container. Proper dosing saves costs and minimises environmental impact.

Application and Dosing



Dose in relation to application and degree of soil. Follow below instructions.



Floor preparation: strip the floor, remove all dirt and old dispersion layers.



Initial treatment: apply 2-3 thin and uniform layers. Drying time between the applications at least 30min.



Large areas: work in sections and apply wet in wet. Usage: approx. 2 L / 100 m².



Coating refreshment: remove slight scratches using the spray-cleaner-method and a highspeed machine with red pad.

Sales units

Order No. 714289 2 x 5 L

Your trusted partner on site

pH-Value

