

## TECHNICAL SPECIFICATIONS

**DEVICE:** lotus<sup>®</sup> PRO High Capacity Dispenser | **SOLUTION:** Stabilized Aqueous Ozone (SAO)

The lotus<sup>®</sup> PRO High Capacity Dispenser turns ordinary tap water into **Stabilized Aqueous Ozone (SAO)**, a powerful natural cleaner and sanitizer. SAO is made on demand with continuous flow for spray bottles, mop buckets, and auto scrubbers - killing germs\* while cleaning. It provides residue-free performance for a longer lasting clean and low slippage on even the smoothest floors. Safe on natural wood and stone.

### STABILIZATION MODULE

Get hours of cleaning power with the Stabilization Module.

Turns ordinary tap water into a long-lasting, natural cleaner and sanitizer using patented Stabilized Aqueous Ozone technology that keeps more ozone in solution for longer periods.

*Items may not appear exactly as shown*

US and International Patents and Patent Pending.  
lotus<sup>®</sup> and Tersano<sup>™</sup> are trademarks of Tersano Inc.



### REGULATORY INFORMATION

**EPA Site Registration No.:** 89093-CAN-001

**NSF International Registration No.:** 152236

**CSA:** Tested to CSA Standard E60335-1/A4E:03 by TUV

**EPA:** DIS/TSS-4 sanitizer test passed

**UL:** Tested to UL Standard 979 by TUV

**Green Standard:** Meets Green Seal<sup>™</sup> GS-37 and GS-53 standards

**Europe:** CE and EN 60335-1/A2:2006 compliant

**OSHA:** Off-gas O<sub>3</sub> < .01 ppm PEL

**ASSE:** Tested to ASSE Standard 1055-2009 by CSA Group

**California Code:** Exceeds regular limits on VOC's

**FDA Safe Designation:** 21CFR184.1563

Zero global warming; Zero ozone depletion; Zero VOCs

### TECHNICAL SPECIFICATIONS

**Dimensions:** 17.5" x 14.5" x 7"

**Weight:** 25lbs

**Flow:** Continuous - 30 min. shut off safety feature

**Rate:** up to 3 gals/min

**Power:** Standard 110V (Power consumption about 90 watts)

Built-in mechanical backflow prevention

**MODEL #**

**LQFC425K**

**LQFC825K**

**Sanitizing Time**

Up to 4 hrs

Up to 24 hrs

**Cleaning Time**

Up to 3 days

Up to 6 days

**Cartridge Life**

Series I - 6,000 litres <sup>1</sup>

Series II - 3,000 litres <sup>1</sup>

<sup>1</sup> Based on a flow rate of 12 lpm

For support reference, visit our website at [www.tersano.com](http://www.tersano.com)

CERTIFIED • PROVEN • POWERFUL