
## 274 CiTi™ 14 mm unbacked



- Thick coils (strand diameter 1 mm) of extruded from 100% PVC, this mat of 14 mm thickness unbacked scrapes dirt and moisture off shoes, allowing it to fall in to the mat and not be tracked in to the building.
- For placement interior facility entrances or recessed wells.
- Durable flexible material is ultra violet resistant, performs well in different climates and adapts to any surface.
- Unbacked version allows dirt and water to flow through in outdoor areas (does not absorb water).
- Suitable for heavy traffic conditions
- Slip resistance tested R11 according to DIN EN 130501-1 and BRG181.
- Vacuum clean or wash off with hose.
- Free of toxic DOP and DMF.



















## 274 CiTi 14 mm unbacked

		PRODUCT SPECIFICATIONS	
Designation	Dust Control Matting		
Description	Non-absorbent / scrape vinyl mat		
Material	Thick coils (strand diameter 1 mm) of extruded from 100% PVC		
Process	Extrusion		
Category	Outdoor - Non-absorbent - Spaghetti		
Recommended use	Outdoor - heavy foot traffic		
Colours	Charcoal, Green, Brown, Red, Grey, Black, Navy-Blue		
Weight	4.8 kg/m <sup>2</sup>		
Thickness	14 mm		
Standard sizes	120 cm x 18 m 120 cm x 6 m		
Custom sizes	120 cm per linear meter		
Special remarks	UV resistant		
		PRODUCT TESTING	
	Tests	Norms	Results
Abrasion resistance		ASTM D3884	
Colour fastness to light		AATCC 16E	
Accelerated wear test by sim floor machine		U.S.	
Accelerated soiling		U.S.	
Anti-slip		DIN51130 BGR181	R11
Water retention		U.S	
Sanitary epidemiologic test		GN 2.1.6.1338-03 MCL GN 2.1.6.2309-07 OBUV	Pass - Certificate no. 77.01.16.229.P.044983.07.
		FIRE TESTING	
	Surface Flammability	ASTM D2859	
	Classification of the reaction to fire performance	DIN EN 13501-1	Bfl - S1
Sustainability		<ul> <li>Recyclable material</li> <li>REACH compliant (Registration, Evaluation, Authorization and restrictions of Chemicals)</li> <li>Contributes to cleaner environment by reducing need of cleaning chemicals</li> </ul>	

