

## 265 Wayfarer® 10 mm backed



- Standard size CiTi™ mat, 10 mm backed, for loose lay, with pressed beveled borders on all four sides.
- Vinyl loops scrape dirt and moisture off shoes, allowing it to fall in to the mat and not be tracked in to the building (does not absorb water).
- Durable flexible material is ultra violet resistant, performs well in different climates and adapts to any surface.
- This backed version ensures minimum movement.
- Fine coils (strand diameter 0.35 mm) of extruded from 100% PVC.
- Suitable for light to medium conditions.
- For placement interior facility entrances or recessed wells.
- Vacuum clean or wash off with hose.
- Free of toxic DOP and DMF.

## 265 Wayfarer® 10 mm backed

| PRODUCT SPECIFICATIONS                     |  |  |          |
|--|--|--|----------|
| Designation                                | Dust Control Matting   |  |          |
| Description                                | « Spaghetti » matting with backing   |  |          |
| Type                                       | Non-absorbent / scrape vinyl mat   |  |          |
| Material                                   |  |  |          |
|  | Top  | Fine coils (strand diameter 0,35 mm) of extruded from 100% PVC |          |
|  | Backing  | Vinyl  |          |
| Process                                    | Extrusion  |  |          |
| Category                                   | Outdoor Non-absorbent - Spaghetti  |  |          |
| Recommended use                            | Out / indoor - light to medium foot traffic  |  |          |
| Colours                                    | Grey   |  |          |
| Weight                                     | 4 kg/m <sup>2</sup>  |  |          |
| Thickness                                  | 10 mm  |  |          |
| Standard sizes                             | 90 cm x 150 cm<br>120 cm x 180 cm  |  |          |
| Custom sizes                               |  |  |          |
| Special remarks                            | UV resistant   |  |          |
| PRODUCT TESTING                            |  |  |          |
| Tests                                      | Norms  | Results  |          |
| Abrasion resistance                        | ASTM D3884   | 15.6 % weight loss   |          |
| Colour fastness to light                   | AATCC 16E  |  |          |
| Accelerated wear test by sim floor machine | U.S.   | 5  |          |
| Accelerated soiling                        | U.S.   | 2.5  |          |
| Anti-slip                                  | DIN51130 BGR181  | R11  |          |
| Water retention                            | U.S  | 2.9 l/m <sup>2</sup>   |          |
| Sanitary epidemiologic test                | GN 2.1.6.1338-03 MCL<br>GN 2.1.6.2309-07 OBUV  | Pass - Certificate no.<br>77.01.16.229.P.044983.07.            |          |
| FIRE TESTING                               |  |  |          |
|  | Surface Flammability   | ASTM D2859   | Pass     |
|  | Classification of the reaction to fire performance   | DIN EN 13501-1   | Bfl - S1 |
| Sustainability                             | <ul style="list-style-type: none"> <li>• Recyclable material</li> <li>• REACH compliant ( Registration, Evaluation, Authorization and restrictions of Chemicals)</li> <li>• Contributes to cleaner environment by reducing need of cleaning chemicals</li> </ul> |  |          |